

COMPRESSORI DWM SCROLL

SCROLL DWM COMPRESSORS

COMPRESSEURS DWM SCROLL

**CENTRALE FRIGORIFERA SERIE "PANZER"
COOLING STATION "PANZER" SERIE
CENTRALE FRIGORIFIQUE SERIE "PANZER"**

**GAS R 404-A PER NORMALE TEMPERATURA
GAS R 404-A FOR MEDIUM TEMPERATURE
GAZ R 404-A POUR MOYENNE TEMPERATURE**



CODE	COMPRESSOR			CAPACITY KW		RIC. LIQUIDO LIQ. RECEIVER LITRI LITRES	CATEGORIA PED	TUBI DI COLLEGAMENTO PIPE FITINGS				DIMENSIONE DIMENSION			PESO WEIGHT KG.	LISTINO PREZZI PRICE LIST PRIX COURANT EURO
	MODEL	N°	ASS. KW	-5°C	-10°C			a mm.	b mm.	c mm.	d mm.	L mm.	P mm.	H mm.		
PCEC-N 30..	ZS- 21 K4E	3	7,40	17,25	14,60	30	2	28	22	16	35	2200	800	1350	380	
PCEC-N 35..	ZS- 26 K4E	3	8,05	21,75	18,3	30	2	28	22	16	35	2200	800	1350	500	
PCEC-N 40..	ZS- 30 K4E	3	10,05	25,55	21,4	30	2	28	22	16	42	2200	800	1350	530	
PCEC-N 50..	ZS- 38 K4E	3	12,08	31,28	26,35	48	2	35	22	22	42	2200	800	1350	620	
PCEC-N 60..	ZS- 45 K4E	3	14,25	37,35	31,45	48	2	35	22	22	42	2200	1050	1350	720	
PCEC-N 75..	ZS- 56 K4E	3	17,75	45,15	37,94	48	3	35	22	22	54	2600	1050	1350	890	
PCEC-N 100..	ZS- 75 K4E	3	23,25	63,08	53,25	60	3	35	28	22	54	2600	1050	1350	1150	
PCEC-N 130..	ZS- 92 K4E	3	30,60	77,68	65,34	60	3	35	28	22	54	2600	1200	1350	1290	
PCEC-N 150..	ZS- 11 M4E	3	34,50	90,45	75,95	60	3	42	35	22	54	2600	1200	1350	1425	
PCEC-N 160..	ZS- 92 K4E	4	40,80	103,57	87,12	90	3	42	35	28	2x42	3200	1300	1350	1590	
PCEC-N 200..	ZS- 11 M4E	4	46,00	120,6	101,27	90	3	42	35	28	2x42	3200	1300	1350	1820	

N.B. LE CENTRALI SONO PRESSURIZZATE CON AZOTO

The central stations are pressurized with nitrogen

Centrales pressurisé avec azote

SU RICHIESTA:

INSONORIZZAZIONE CON LASTRA AFONA
RICEVITORE DI LIQUIDO MAGGIORATO
PREDISPOSIZIONE SBRINAMENTO A GAS CALDO
VOLTAGGIO DIFFERENTE
CONDENSATORE REMOTO O A BORDO MACCHINA
COMPONENTI O APPLICAZIONI NON IN DOTAZIONE STANDARD
IMBALLLO

ON REQUEST:

SOUND PROOF MATERIAL
OVERSIZED LIQUID RECEIVER
HOT GAS DEFROSTING
DIFFERENT VOLTAGE
REMOTE CONDENSER OR ON THE MACHINE
COMPONENETS OR APPLICATIONS OUT OF
STANDARD
PACKING

SUR DEMANDE :

INSONORISATION
BOUTEILLE DE LIQUIDE MAJEURE'
DEGIVRAGE A' GAZ CHAUDE,
TENSION DIFFERENT
CONDENSATEUR A' DISTANCE OU' SUR LA
CENTRALE - COMPONENETS OU APPLICA-
TIONS NE PAS STANDARD
EMBALLAGE

COMPRESSORI DWM SCROLL

SCROLL DWM COMPRESSORS

COMPRESSEURS DWM SCROLL

**CENTRALE FRIGORIFERA SERIE "PANZER"
COOLING STATION "PANZER" SERIE
CENTRALE FRIGORIFIQUE SERIE "PANZER"**

**GAS R 404-A PER BASSA TEMPERATURA
GAS R 404-A FOR LOW TEMPERATURE
GAZ R 404-A POUR BASSE TEMPERATURE**



CODE	COMPRESSOR			CAPACITY KW			RIC. LIQUIDO LIQ. RECEIVER LITRI LITRES	CATEGORIA PED	TUBI DI COLLEGAMENTO PIPE FITINGS				DIMENSIONE DIMENSION			PESO WEIGHT KG.	LISTINO PREZZI PRICE LIST PRIX COURANT EURO
	MODEL SCROLL	N°	ASS. KW	-30°C	-35°C	-40°C			a mm.	b mm.	c mm.	d mm.	L mm.	P mm.	H mm.		
PCES-B 30..	ZF- 09 K4E	3	7,40	6,78	5,35	4,15	19	2	22	18	16	35	2200	800	1350	380	
PCES-B 35..	ZF- 11 K4E	3	8,48	8,42	6,72	5,19	19	2	22	18	16	35	2200	800	1350	425	
PCES-B 40..	ZF- 13 K4E	3	10,26	9,62	7,75	6,1	30	2	22	18	16	35	2200	800	1350	600	
PCES-B 50..	ZF- 15 K4E	3	11,92	11,75	9,7	7,48	30	2	28	22	22	42	2200	800	1350	700	
PCES-B 60..	ZF- 18 K4E	3	14,11	14,46	11,6	9,15	48	2	28	22	22	42	2200	1050	1350	790	
PCES-B 75..	ZF- 24 K4E	3	18,90	18,16	14,38	11,05	48	3	28	22	28	54	2600	1050	1350	920	
PCES-B 100..	ZF- 33 K4E	3	23,80	25,09	19,45	14,2	60	3	42	35	28	54	2600	1050	1350	1150	
PCES-B 130..	ZF- 40 K4E	3	30,40	31,04	24,24	18,2	60	3	42	35	28	64	3100	1200	1350	1290	
PCES-B 150..	ZF- 48 K4E	3	34,52	35,05	28,01	22	60	3	42	35	28	64	3100	1200	1350	1325	
PCES-B 160..	ZF- 40 K4E	4	40,53	41,4	33,32	24,27	80	3	54	42	28	2x42	3100	1300	1350	1460	
PCES-B 200..	ZF- 48 K4E	4	46,03	46,74	37,35	29,33	80	3	54	42	35	2x42	3600	1300	1350	1590	

N.B. LE CENTRALI SONO PRESSURIZZATE CON AZOTO

The central stations are pressurized with nitrogen

Centrales pressurisé avec azote

SU RICHIESTA:

INSONORIZZAZIONE CON LASTRA AFONA
RICEVITORE DI LIQUIDO MAGGIORATO
PREDISPOSIZIONE SBRINAMENTO A GAS CALDO
VOLTAGGIO DIFFERENTE
CONDENSATORE REMOTO O A BORDO MACCHINA
COMPONENTI O APPLICAZIONI NON IN DOTAZIONE STANDARD
IMBALLO

ON REQUEST:

SOUND PROOF MATERIAL
OVERSIZED LIQUID RECEIVER
HOT GAS DEFROSTING
DIFFERENT VOLTAGE
REMOTE CONDENSER OR ON THE MACHINE
COMPONENETS OR APPLICATIONS OUT OF
STANDARD
PACKING

SUR DEMANDE :

INSONORISATION
BOUEILLE DE LIQUIDE MAJEURE'
DEGIVRAGE A' GAZ CHAUDE
TENSION DIFFERENT
CONDENSATEUR A' DISTANCE OU' SUR LA
CENTRALE - COMPONENETS OU APPLICA-
TIONS NE PAS STANDARD
EMBALLAGE